

EFFICIENT LINE


EASY STANDARD



Contact

Power in every detail

The **EASY STANDARD** breathing air compressors stand out for their robustness and reliability. Equipped with two high-pressure hose connections, these compressors are powered by a robust electric motor, available in both single-phase and three-phase versions. The pump units, built for long-lasting performance, and the fully metal compact frame ensure exceptional durability. Available options include external charging panels, an electric panel with automatic condensate drain, a pressure gauge with auto-stop function, and convenient handles for easy transport.



Technical data

Type of gas	Breathing air EN 12021
Intake pressure	Atmospheric / max 300 millibar
Working pressure	232 bar / 300 bar / 330 bar
Max working pressure	232 bar (Single-phase electric) / 420 bar (Three-phase electric)
Permissible ambient temperature range	-10° C ÷ +40° C
Permissible altitude	0 ÷ 1.500 m SLM
Max permissible tilt	6°
Oil	Synthetic Coltri Oil ST 755
Oil change interval	1 year / 1.000 h
Frame	Steel - Colour Black RAL 9005 - Powder coating painting - Scratch proof

Compressor

	125 EM	150 EM	315 ET
Charging rate Measured during 10 liters cylinder filling from 0-200 bar tolerance +/- 5% at + 20 ° C ambient temperature.	125 l/min 7.5 m³/h 4.4 cfm	150 l/min 9 m³/h 5.3 cfm	315 l/min 18.9 m³/h 11.1 cfm
Purification System	Maxifilter		
Cooling air flow	1.710 m³/h	1.710 m³/h	2.180 m³/h
Weight¹	98 kg - 216 lb	98 kg - 216 lb	110 kg - 242.5 lb
Dimensions (W x D x H)¹	84.9 × 48.8 × 65.3 cm - 33.4 × 19.2 × 25.7 in		

¹ Standard model. Dimensions and weight may vary depending on accessories.


Electric motor

	125 EM	150 EM	315 ET	
Type	Single-phase electric		Three-phase electric	
Power	3 kW - 4 Hp	4 kW - 5.5 Hp	5,5 kW - 7.5 Hp	
Operating voltage/frequency Different voltage / frequency available on request.	230 V, 60 Hz	220 V, 50 Hz	400 V, 50 Hz	440 V, 60 Hz
Rated current	20 A	25,2 A	12,6 A	
Speed (RPM)	2.800	2.850	2.850	3.420
Protection class	IP55			

The IP55 protection class, compliant with IEC 60034-5, guarantees protection against dust deposits and water jets from any direction.

Technical data pumping unit MCH 8/9/16

	125 EM	150 EM	315 ET
Charging rate	125 l/min 7.5 m³/h 4.4 cfm	150 l/min 9 m³/h 5.3 cfm	315 l/min 18.9 m³/h 11.1 cfm
Speed (RPM)	1.500	1.440	1.600
Number of stages	3		
Number of cylinders	3		
Cylinder bore 1st stage	60 mm	70 mm	95 mm
Cylinder bore 2nd stage	38 mm		
Cylinder bore 3rd stage	14 mm		
Stroke	40 mm		
Direction of rotation from flywheel side	Counter clockwise (left)		
Drive type	V-belt A type		
Intermediate pressure 1st stage	~ 6 bar		
Intermediate pressure 2nd stage	~ 45 bar		
Oil sump capacity	1,8 liters		
Max intake pressure	1,3 bar (absolute) / 300 millibar - 4,35 psi		







Splash lubrication with conrod pin immersed in oil




Suction filter: 10 µm



Pipes, fitting and nuts in stainless steel AISI 316



Intermediate condensate separator after the second stage



High pressure final condensate separator



Safety valves after each stage of compression




Die-cast aluminium cylinders with barrel coating in nicasil



Forged aluminum connecting rods




Forged steel crankshaft




Stainless steel second and third stage valves



Roller Bearings for intensive work load



Third stage in tempered steel with 5 piston rings in special cast iron



Second and third stage with pushing pistons to eliminate lateral forces on the pistons



CE certification

Standard equipment

Purification system Maxifilter

MAXIFILTER cartridge repackable or disposable



Purification system	Maxifilter
Operating pressure (Standard)	250 bar / 330 bar / 360 bar
Operating pressure max. (PS)	420 bar
Processable air capacity (air inlet temperature in the filter 20° C at 300 bar) ¹	890 m³

¹ When using a filter cartridge without HOPCALITE CO CATALYST.
If a cartridge with CO removal is used, the process air capacity is reduced by about 20%.

Condensate separation system

- Interstage separator after 2nd stage
- Final separator for the removal of oil/water condensate
- Final safety valve, fitted to separator housing
- Pressure maintaining/non return valve



Contamination	Maximum content as per DIN EN 12021:2014	Air quality*
H ₂ O	25 mg/m	≤ 10 mg/m
CO	5 ppm(v)	≤ 4
CO ₂	500 ppm(v)	≤ 500
Oil	0,5 mg/m	≤ 0,5 mg/m

* Measured at our facility using ASCO HORA 160 ANALYZER.

- Only with special filter cartridge with HOPCALITE CO CATALYST. and up to a maximum concentration of 25 ppm CO in intake air. The compressed clean breathing air then contains a maximum of 5 ppm CO.
- The level of CO₂ in the intake air must not exceed the maximum level of CO₂ as per EN 12021:2014.
- Reported values exceed standards:
 - ISO 8573-1 class 3 for particles
 - ISO 8573-1 class 1 for humidity
 - ISO 8573-1 class 1 for oil.



Filling connection

2 Filling connection to choose from: DRV DIN 232 bar, INT/YOKE DRV 232 bar and DRV DIN 300 bar.



Filling hose

Optional



C-Monitor








Automatic condensate drain system with timer



Carrying handles

Application fields



Aerotecnica Coltri S.p.A.

Via dei Colli Storici, 177
25015 Desenzano del Garda - Brescia - Italy

Tel. +39 030 9910301
+39 030 9910297

info@coltri.com



Printed on paper from
sustainably managed forests



coltri.com

Visit our
showroom in
Virtual Reality



coltri.com/showroom



COLTRI[®]
COMPRESSORS