

EFFICIENT LINE

ERGO 285 SK FA


PETROL



Contact

Maximum efficiency in motion

Practical and lightweight, **ERGO 285 SK FA** combines robustness and great operational efficiency. Equipped by a powerful pumping unit, powered by Kohler petrol motor. It is equipped by autostop with fixed pressure switch, automatic condensate drain and electric start with battery. There are two connections for high pressure hoses (from 232 to 330 bar) and a Maxifilter filter system. The C-Monitor, the digital hour meter and the remote charging panels are available as optional.



Technical data

Type of gas	Breathing air EN 12021
Intake pressure	Atmospheric / max 300 millibar
Working pressure	232 bar / 300 bar / 330 bar
Max working pressure	420 bar
Permissible ambient temperature range	-10° C ÷ +40° C
Permissible altitude	0 ÷ 1.500 m SLM
Max permissible tilt	6°
Oil	Synthetic Coltri Oil ST 755
Oil change interval	1 year / 1.000 h
Frame	Steel - Colour Black RAL 9005 - Powder coating painting - Scratch proof

Compressor

	285 SK FA
Charging rate Measured during 10 liters cylinder filling from 0-200 bar tolerance +/- 5% at + 20 ° C ambient temperature.	285 l/min 17.1 m³/h 10.1 cfm
Purification System	Maxifilter
Cooling air flow	1.440 m³/h
Weight¹	172 kg - 379.2 lb
Dimensions (W x D x H)¹	124 × 65 × 77 cm - 48.8 × 25.6 × 30.3 in


¹ Standard model. Dimensions and weight may vary depending on accessories.

Engine

	285 SK FA
Type	Petrol Kohler CH 440
Power	9 kW - 12 Hp
Speed (RPM)	3.600

Technical data pumping unit MCH 16

	285 SK FA
Charging rate	285 l/min
Measured during 10 liters cylinder filling from 0-200 bar	17.1 m³/h
tolerance +/- 5% at + 20 ° C ambient temperature.	10.1 cfm
Speed (RPM)	1.520
Number of stages	3
Number of cylinders	3
Cylinder bore 1st stage	95 mm
Cylinder bore 2nd stage	38 mm
Cylinder bore 3rd stage	14 mm
Stroke	40 mm
Direction of rotation (from flywheel side)	Counter clockwise (left)
Drive type	V-belt A type
Intermediate pressure 1st stage	~ 6 bar
Intermediate pressure 2nd stage	~ 45 bar
Oil sump capacity	1,8 liters
Max intake pressure	1,3 bar (absolute) / 300 millibar - 4,35 psi







Splash lubrication with conrod pin immersed in oil




Suction filter: 10 µm




Pipes, fitting and nuts in stainless steel AISI 316



Intermediate condensate separator after the second stage



High pressure final condensate separator



Safety valves after each stage of compression




Die-cast aluminium cylinders with barrel coating in nicasil



Forged aluminum connecting rods




Forged steel crankshaft




Stainless steel second and third stage valves



Roller Bearings for intensive work load



Third stage in tempered steel with 5 piston rings in special cast iron



Second and third stage with pushing pistons to eliminate lateral forces on the pistons



CE certification

Standard equipment

Purification system Maxifilter

MAXIFILTER cartridge repackable or disposable



Purification system	Maxifilter
Operating pressure (Standard)	250 bar / 330 bar / 360 bar
Operating pressure max. (PS)	420 bar
Processable air capacity (air inlet temperature in the filter 20° C at 300 bar) ¹	890 m ³

¹ When using a filter cartridge without HOPCALITE CO CATALYST.
If a cartridge with CO removal is used, the process air capacity is reduced by about 20%.

Condensate separation system

- Interstage separator after 2nd stage
- Final separator for the removal of oil/water condensate
- Final safety valve, fitted to separator housing
- Pressure maintaining/non return valve



Contamination	Maximum content as per DIN EN 12021:2014	Air quality*
H ₂ O	25 mg/m	≤ 10 mg/m
CO	5 ppm(v)	≤ 4
CO ₂	500 ppm(v)	≤ 500
Oil	0,5 mg/m	≤ 0,5 mg/m


- * Measured at our facility using ASCO HORA 160 ANALYZER.
- Only with special filter cartridge with HOPCALITE CO CATALYST. and up to a maximum concentration of 25 ppm CO in intake air. The compressed clean breathing air then contains a maximum of 5 ppm CO.
 - The level of CO₂ in the intake air must not exceed the maximum level of CO₂ as per EN 12021:2014.
 - Reported values exceed standards:
 - ISO 8573-1 class 3 for particles
 - ISO 8573-1 class 1 for humidity
 - ISO 8573-1 class 1 for oil.

Filling connection

2 Filling connection to choose from: DRV DIN 232 bar with gauge, DRV INT/YOKE 232 bar and DRV DIN 300 bar with gauge.



Electric starter with battery



Automatic shutoff with pressure switch



Automatic condensate drain

Optional








C-Monitor



Digital hour meter

Application fields



Aerotecnica Coltri S.p.A.

Via dei Colli Storici, 177
25015 Desenzano del Garda - Brescia - Italy

Tel. +39 030 9910301
+39 030 9910297

info@coltri.com



Printed on paper from
sustainably managed forests



coltri.com

Visit our
showroom in
Virtual Reality



coltri.com/showroom



COLTRI®
COMPRESSORS